



a **MUELLER** brand

DUCTILE IRON SERVICE SADDLES SPECIFICATION

Product Specifications

1. The service saddles shall be tested and conform to all applicable standards, including ANSI/AWWA C-800.
2. The service saddles shall be available for use on cast iron, ductile iron, steel, AWWA C900 PVC plastic pipe.
3. The service saddles shall be one of the following strap types:
 - a. A single strap style for all 1/2" through 1" service lines on nominal size mains 2" through 12" in size and 1/2" through 2" line services on nominal size mains 4" through 12".
 - b. A double strap style for all 3/4" through 2" service lines on nominal size mains 4" through 24" in size.
 - c. A single strap style for all 1/2" through 1" service lines for nominal sized mains 2" through 12" and a double strap style for all 3/4" through 2" service lines on nominal size mains 4" through 24" in size.
4. The service saddles shall have bodies composed of ductile iron, ASTM A395 alloy.
5. The service saddles shall have a coating of NSF approved Rilsan nylon.
6. The service saddle straps and nuts shall be composed of one of the following:
 - a. A zinc plated steel type with a flattened area to provide a gripping surface on the pipe.
 - b. A 304L stainless steel type with a flattened area to provide a gripping surface on the pipe. The nuts shall be fluorocarbon or PTFE coated.
7. The service saddle straps shall have rolled threads to facilitate installation of the nuts.
8. The service saddles shall have a maximum working pressure of 250 psi (1724 kPa) for single strap saddles and a maximum working pressure of 500 psi (3447 kPa) for double strap saddles.
9. The service saddle outlet shall be sealed by a nitrile rubber O-ring.

For more information about us, or to view our full line of products, please visit www.mueller-international.com or call International Customer Service at:

UK: +44.1438.487410 Dubai: +971.4.214.6640 Singapore: +65.6816.3088 USA: +1 800.423.1323 International@muellerwp.com

Mueller refers to one or more of Mueller Water Products, Inc. a Delaware corporation ("MWP"), and its subsidiaries. MWP and each of its subsidiaries are legally separate and independent entities when providing products and services. MWP does not provide products or services to third parties. MWP and each of its subsidiaries are liable only for their own acts and omissions and not those of each other. MWP brands include Mueller®, Echologics®, Hydro Gate®, Hydro-Guard®, HYMAX®, Jones®, Krausz®, Mi.Net®, Milliken®, Pratt®, Pratt Industrial®, Singer®, and U.S. Pipe Valve & Hydrant. Please see muellerwp.com/brands and krauszusa.com to learn more.

© 2021 Mueller Co., LLC. All Rights Reserved. The trademarks, logos and service marks displayed in this document are the property of Mueller Water Products, Inc., its affiliates or other third parties. Products marked with a section symbol (§) are subject to patents or patent applications. For details, visit www.mwppat.com. These products are intended for use in potable water applications. Please contact your Mueller Sales or Customer Service Representative concerning any other application(s).



10. The service saddle shall have a tapping boss with full length threads of one of the following:

- a. An AWWA tapered or "CC" thread.
- b. An AWWA iron pipe thread (F.I.P.T.).

The nylon coated saddles with a single stainless-steel strap shall be HYMAX® DR1S series or approved equal.

The nylon coated saddles with a double stainless-steel strap shall be HYMAX® DR2S series or approved equal.

The nylon coated saddles with a single alloy strap shall be HYMAX® DR1A series or approved equal.

The nylon coated saddles with a double alloy strap shall be HYMAX® DR2A series or approved equal.

